



Eco Accents - 5100 Acrylic Enamel Gloss/Semi-Gloss Technical Data Sheet

PRODUCT DESCRIPTION

Eco Accents 5100 is an extremely durable 100% modified acrylic enamel, which provides excellent adhesion to alkyd gloss and semi-gloss surfaces. For use on most interior surfaces where maximum durability is desired. Also can be used for select exterior applications.

ADVANTAGES

- Zero VOC Content
- Great Hiding Power
- Excellent Touch Up
- Easy Application
- Excellent Sag Resistance
- Water Clean Up
- Qualifies for LEED Credits

USES

- Interior walls and ceilings
- High Traffic areas
- Can be applied to concrete, plaster, drywall, and over wallpaper

RECOMMEND PRIMERS

- Wood - 250 Bondaplex Acrylic Primer or 180 Enamel Undercoat
- Drywall - 690 Vinyl Emulsion Primer
- Masonry - 690 Vinyl Emulsion Primer
- Concrete Block - 3350/650 Block Filler
- Steel/Aluminum/Galvanized - call manufacturer

SURFACE PREPARATION

Surface must be dry and free of chalk, dirt, grease, peeling or flaking paint, oil, mildew and rust.

APPLICATION

Do not apply when air or surface temperature is below 50°F. Apply by brush, roll or spray. Two coats are recommended.

TECHNICAL SPECIFICATION

Colors: All Colors

Vehicle Type: Modified/Acrylic

Solids, by volume: 33.23 +/- 2.0%

Weight, per gallon 10.39 lbs. +/- 2.0%

Coverage: 350-400 Square Feet per Gallon

Flash Point: Not Applicable

Viscosity: 85-95 KU

Dry Time:

To Touch: 1 Hour

To Recoat: 4-6 hours

VOC: 0 Grams/ Liter; trace

Clean Up: Soapy water

See Material Safety Data Sheet for Complete Precautionary Requirements

WARRANTY: The technical data contained herein are true and accurate to the best of our knowledge and are subject to change without prior notice. No guarantee of accuracy is either given or implied. We assume no responsibility for coverage performance or injuries resulting from use. Liability, if any, is limited to product replacement. No other warranty or guarantee of any kind is made by seller, express or implied, statutory, by operation of law, or otherwise, including merchantability and fitness for a particular purpose.

Additional Info: Keep from freezing. Stir thoroughly prior to use and every 15 minutes during application. Boxing is recommended to maintain uniform tinting.

Revised 10/02/10