



Eco Accents Primer 5690 Technical Data Sheet

PRODUCT DESCRIPTION

Eco Accents Primer 5690 is a vinyl emulsion primer especially designed to lay down the nap of drywall. It has excellent enamel hold out properties that prevent variation of sheen in finish coats. 5690 is a low VOC and low odor formulation.

USES

- As primer for new sheetrock, drywall, plaster, concrete, brick, wood or previously painted porous surfaces
- Use with Eco-Accents interior latex, Bio-Shield Interior Coating 5100 semi-gloss and Bio-Shield Interior Coating 5400 eggshell paints.

SURFACE PREPARATION

Previously Painted Surfaces

Remove all dust, dirt, grease, wax and oil with household detergent. Remove any loose, peeling or flaking paint. Patch holes and cracks with appropriate patching compound, and smooth and dust. Dull glossy surfaces by light sanding. Areas of a previously painted surface that have peeled to expose the substrate should be primed with Eco Accent Primer before applying topcoat.

APPLICATION

Do not apply when air or surface temperature is below 50°F. Apply by brush, roll or spray.

TECHNICAL SPECIFICATION

Colors: White

Vehicle Type: Vinyl Acrylic

Finish: Flat

Solids, by volume: 30.86 +/- 2.0%

Weight, per gallon 11.08 lbs.

Coverage: 275-300 Square Feet per Gallon

Flash Point: Not Applicable

Viscosity: 95-100 KU

Dry Time:

To Touch: 30 Minutes

To Recoat: 2-4 Hours

VOC: <10 Grams/ Liter

Clean Up: Water

THINNING

Use water if necessary.

SHELF-LIFE

12 Months.

See Material Safety Data Sheet for Complete Precautionary Requirements

WARRANTY: The technical data contained herein are true and accurate to the best of our knowledge and are subject to change without prior notice. No guarantee of accuracy is either given or implied. We assume no responsibility for coverage performance or injuries resulting from use. Liability, if any, is limited to product replacement. No other warranty or guarantee of any kind is made by seller, express or implied, statutory, by operation of law, or otherwise, including merchantability and fitness for a particular purpose.

Additional Info: Keep from freezing. Stir thoroughly prior to use and every 15 minutes during application.
Revised 10/02/10